

**Range: Bowral 76**

**Colour: Chillingham White**

**SKU: 280080010780000136100**

## Technical Data

<b>Length (mm)</b>	230
<b>Width (mm)</b>	110
<b>Height (mm)</b>	76
<b>Dimensional Category</b>	DW1
<b>Core Volume (%)</b>	Solid
<b>Units per Square Metre</b>	48.5
<b>Pack Size</b>	384
<b>Characteristic Unconfined Compressive Strength (f 'uc) MPa</b>	>8
<b>Maximum Cold Water Absorption (%)</b>	<15
<b>Initial Rate of Absorption (IRA) (kg/m<sup>2</sup> min)</b>	1 to 8
<b>Coefficient of Expansion e'Factor (mm/m)</b>	<1.2

<b>Durability Class</b>	Exposure Grade
<b>Liability to Efflorescence</b>	Nil to slight
<b>Lime Pitting Liability</b>	Nil to slight
<b>Solar Absorption</b>	0.343
<b>LRV</b>	66.44
<b>FRL</b>	180/180/90
<b>Basix</b>	Light
<b>Place of Manufacture</b>	New South Wales
<b>Product Warranty</b>	100 Years
<b>Solar Absorption</b>	0.343
<b>Meter squared</b>	48.5
<b>Average Weight / Unit (kg)</b>	3.8

Please note: FRL applies up to 3m high - restrained on top and bottom.