

Range: Bowral Highlands

Colour: Meryla

SKU: 281070019200000136150

Technical Data

Please note: FRL applies up to 3m high - restrained on top and bottom.

| | |
|---|-------------------|
| Length (mm) | 230 |
| Width (mm) | 110 |
| Height (mm) | 76 |
| Dimensional Category | DW1 |
| Core Volume (%) | Solid |
| Units per Square Metre | 48.5 |
| Pack Size | 384 |
| Characteristic Unconfined Compressive Strength (f _{uc}) MPa | >8 |
| Maximum Cold Water Absorption (%) | 15 |
| Initial Rate of Absorption (IRA) (kg/m ² min) | 1 to 8 |
| Coefficient of Expansion e'Factor (mm/m) | 1.2 |
| Durability Class | Exposure Grade |

| | |
|----------------------------|-------------------------|
| Liability to Efflorescence | BOWRAL BRICKS Slight |
| Lime Pitting Liability | Slight |
| Solar Absorption | 0.4 |
| LRV | 27.8 |
| FRL | 180/180/90 |
| Basix | Light |
| Place of Manufacture | New South Wales |
| Product Warranty | 100 Years |
| Solar Absorption | 0.4 |
| Meter squared | 48.5 |
| Weight | 3.8 |

Please note: FRL applies up to 3m high - restrained on top and bottom.